

HOOVER TREATED WOOD PRODUCTS, INC

TECHNICAL NOTE

FOR ADDITIONAL INFORMATION: www.frtw.com or 1-800-TEC-WOOD (832-9663)

CUTTING, RIPPING and MILLING PYRO-GUARD® and EXTERIOR FIRE-X®

Underwriters Laboratories Inc. (UL) allows basic cutting of ***PYRO-GUARD®*** and ***EXTERIOR FIRE-X®*** fire retardant treated lumber, plywood, and Engineered Wood Products (EWP). However, UL does restrict ripping and milling of lumber, since these operations could affect surface burning characteristics. Below is a description of what is and is not allowed by UL.

- **Cutting of lumber and Engineered Wood Products (EWP) to length:** cross-cutting and end cuts are allowed. Holes and joints such as tongue and groove, bevel, scarf and lap are also allowed. Corbels on rafter tails are allowed.
- **Ripping of lumber:** along the length, such as ripping a 2x4 into 2x2's is not permitted. Similarly, cutting of stair stringers after treatment should not be done because the effect is similar to ripping.
- **Milling or resurfacing of lumber:** not allowed. If special shapes or thickness are required, milling should be done prior to treatment.
- **Cutting of plywood in any direction:** allowed without restriction.
- **Light sanding of lumber, plywood, or Engineered Wood Products (EWP):** is permitted to remove raised grain or to prepare for finishing.
- **End coating is not required.**

DISCLAIMER OF LIABILITY FOR RELIANCE ON INFORMATION PROVIDED BY HOOVER TREATED WOOD PRODUCTS, INC.: The information contained herein is true and accurate to the best of our knowledge, but is provided without warranty or guarantee. Since the conditions of use are beyond our control, Hoover Treated Wood Products, Inc. ("Hoover") disclaims all liability and assumes no legal responsibility for damages resulting from use of or reliance upon the information contained herein.